



## 1/4 HP AIR CIRCULATORS

*Pedestal & Wall Mount*

**MOTOR:** 1/4 HP, 3 Speed, 120V, 1 Phase, ball-bearing, open ventilated, permanently lubricated, permanent split capacitor

**SWITCH:** Pull Chain

**CORD:** 9' long SJT type 3 conductor

**GUARD:** Coated steel with retaining clips

**POLE:** Adjusts center of fan from 43" to 60"



WALL MOUNT

PEDESTAL MOUNT



MODELS	BLADE SIZE	FAN TYPE	FAN MOUNT	MOTOR HP	CFM MAX VELOCITY	AMPS (HIGH)
1012-0016	30"	Fixed	Pedestal	1/4	6,700	2.4
1012-0011	25"	Oscillating			5,400	1.5
1012-0021	30"		6,700		2.0	
1012-0041	24"		Wall		5,400	1.5
1012-0043	30"	6,700			2.0	

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

## DIRECT DRIVE PORTABLE BLOWERS

**MOTOR:** 1/3 HP, 2 speed, 120V, 3.6 amp, ball-bearing, ventilated, lubricated

**BLADE:** Aluminum


**CORD:** 6' long SJT type 3 conductor

**GUARD:** Spiral Wire (front & rear)

**WHEELS:** 5" rubber

**HOUSING:** 20 gauge steel powder coated



STANDARD MODEL (CPB 36-D) 

MODEL #	CFM MAX VELOCITY	CORD LENGTH	SWITCH	WT (LBS)
1012-0051	8,500	10'	ROTARY	70

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY



## COMMERCIAL FLOOR FANS

**MOTOR:** 1/5 HP, 3 speed, sleeve-bearing, ventilated, permanently lubricated

**SWITCH:** Rotary

**CORD:** 7' long, SJT type 3 conductor

**GUARD:** Coated steel with retaining clips



MODEL #	CFM			MAX AMPS	WT (LBS)
	HIGH	MEDIUM	LOW		
1012-0001	1,600	1,480	1,380	1.4	16

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

